

FACULTY OF ENGINEERING

DEPARTMENT OF WATER RESOURCES AND MINING ENGINEERING

FINAL YEAR PROJECT REPORT

DESIGN AND FABRICATION OF A SAFE EMPTYING AND LOADING SYSTEM

By MANDALI DERRICK BU/UP/2018/3641

mandaliderrick@gmail.com

0780-489015 / 0751-201161

A final year project report submitted to the department of water resources Engineering in partial fulfillment of the requirement for the award of the degree of Bachelor of science in water resources engineering

JANUARY 2023

Abstract

In the heavily populated urban slums of Sub-Saharan Africa, feacal sludge (FS), a byproduct of on-site sanitation systems, presents a management difficulty. Pit latrines are the most prevalent and economical onsite sanitation facilities in the Bwaise III zone of downtown Kampala City's informal settlements. However, when latrines fill up, problems arise from a lack of efficient technological choices. This later poses a lot of challenges including those associated with the disposal. Currently, vacuum tankers have an impact on the market, but they are primarily used to empty septic tanks in locations that are easily accessible rather than inaccessible locations where pit latrines and filled manholes are common. Due to accessibility issues, heavy traffic, and vast distances to treatment facilities, the collection and transportation of FS from slums is expensive. In response to the above challenges, a safe emptying and loading system was designed and constructed. The system is cheap, affordable and environmentally friendly. The system is made up of a suction rotary vane compression system and forklift which is a loading device. A suction rotary vane compression system is made up of a metallic drum, the rotary compressor coupled to the engine using a pulley and connected with pipe fittings. The forklift was fabricated from mild steel which is readily available, cheap and can be made from locally available materials and scrap materials. This comprises of mainly hand-winch, the fork and a frame. The prototype was tested at Busitema university workshop and the test results were tabulated, graphs of discharge vs suction time, suction time vs elevation, elevation vs discharge, load vs time were plotted. An economic analysis was carried out and it shows that the project is viable. Therefore, based on the limitations of the current design, further modifications and recommendations are advised.

Declaration

I **Mandali Derrick**, declare that all the material portrayed in this project report is original and has never been submitted in for award of any Degree, certificate, or diploma to any university or institution of higher learning.

Signature



Acknowledgment

I would like to extend my sincere thanks to the almighty GOD who has gifted me with life and has enabled me to reach this academic height as he has been the provider of all the requirements.

Special appreciation goes to Mr. Maseruka Benidicto for imparting in me the knowledge and guidance towards making this research and to exhibit professional morals.

Great thanks to my beloved Parents, relatives and friends for their endless encouragement, financial support and advice given to me in the course of my academic struggle.

Approval

This is to certify that the project report has been carried out under my supervision and this report is ready for submission to the Board of examiners and senate of Busitema University with my approval.

SUPERVISOR:

MR. MASERUKA BENDICTO

Magn-£

SIGNATURE:

DATE:/January.../2023

Table of Contents

Abstract	ii
Declaration	iii
Acknowledgment	iv
Approval	v
List of acronyms	ix
Table of figures	X
List of tables	xi
Chapter one: Introduction	1
1.1: Background of the study	1
1.2: Problem Statement	3
1.3: Objectives	3
1.3.1: Main objective Error! Book	mark not defined.
1.3.2: Specific objectives Error! Book	mark not defined.
1.4: Justification of the Study	3
1.5: Significance of the Study	4
1.6: Scope of the Study	4
1.6.1:Conceptual scope Error! Book	mark not defined.
1.6.2: Geographical scopeError! Book	mark not defined.
1.6.3: Time scope	4
Chapter Two: Literature Review	5
2.1: Introduction	5
2.2: Technologies used in emptying pit latrines	5
2.2.1: Vacuum technologies	5
2.2.2: Non-vacuum technologies	5
2.3: Compressors	6
2.3.1: Classification of compressors	6
2.3.1.1: Positive displacement compressors	7
2.3.1.2: Reciprocating compressors	7
2.3.1.3: Rotary compressors	7
2.3.1.4: Rotary vane compressors	8
2.3.1.5: components of a rotary vane compressor	8
2.3.1.6: Working principle	8
2.4: Forklift	9

2.5: Components of the system	9
2.6: Feacal sludge parameters that affect the flow of feacal sludge	10
2.7: Key words/ main terms	10
Chapter Three: Methods and materials	11
3.1: Introduction	11
3.2: Field visit and site selection	11
3.3: Design	11
3.4: Materials and data collection instruments	11
3.4.1: Secondary data	11
3.4.2: Primary data	11
3.4.3: Conceptual diagrams	12
3.5: Specific Objective One: To design the different parts of the safe emptying a loading system.	
3.5.1: Design calculations	
3.5.2: Designing the components of the fork-lift	
3.5.3: Fork analysis and fork-stress analysis	
3.5.4: Design of the frame	19
3.5.6: Design for ergonomics;	21
3.6: Specific Objective Two: To fabricate and assemble the different parts of the	-
3.6.1: Material selection	
3.6.2: Construction of the safe emptying and loading system	
3.6.3: Techniques and equipment used	
3.6.3.1: Equipment used in the fabrication	
3.6.3.2: Techniques used	
3.6.4: Construction methodology	
3.7: Specific Objective Three: To test the performance of the system	
3.7.1 Testing of the system	
3.8: Specific Objective Four: To perform economic analysis for the project	
3.8.1: Cost estimation	
3.8.2: Cost of materials	
3.8.3: Cost of Labour	
Chapter four: Results and discussion	
4.1: Testing of the suction rotary vane compression system	
4.2: Testing of the forklift	
<u> </u>	

4.3: Integrated testing.	41
4.3.1: Effect of varying fluid densities.	41
4.3.2: Effect of the hosepipe diameter.	41
4.3.3: Effect of the number of the vanes and the pumping head	41
4.3.4: Effect of varying the height to which the load should be lifted on the forklift.	42
Chapter Five: Conclusion and Recommendations	43
5.1: Conclusion	43
5.2: Recommendations	43
References	44
Appendices	46
Appendix I: Production drawings	46
Appendix II: Photos showing different activities, fabricated parts, actual system	50

List of acronyms

Acronyms	Meaning
FSM	Feacal Sludge Management
UNICEF	United Nations International Children's Fund
MDG	Millennium Development Goals
SDG	Sustainable Development Goals
KCCA	Kampala City Council Authority
MAPET	Manual Pit Emptying Technology
SSM	Sewer Sucker Machine
SS	Stainless Steel
PVC	Polyvinyl Chloride
HDPE	High Density Polyethylene
WHO	World Health Organization
UBOS	Uganda Bureau of Statistics
NDP	National Development Plan

Table of figures

Figure 1: Classification of compressors	6
Figure 2: conceptual drawing of a suction rotary compression	on system12
Figure 3: Conceptual drawing of a forklift	12
Figure 4: shows the stress analysis on the fork	18
Figure 5: displacement of the fork	18
Figure 6: stress analysis on the frame	19
Figure 7: Strain analysis on the frame	20
Figure 8: displacement of the frame.	20
Figure 9: Shows the drum and its fittings	
Figure 10: Gas bubbler unit	
Figure 11: Hollow PVC pipe	27
Figure 12: showing the fabricated fork component	
Figure 13: Shows the supporting legs	28
Figure 14: Shows the forklift assembly.	29
Figure 15: forklift assembly	Error! Bookmark not defined.
Figure 16: pump and engine assembly	Error! Bookmark not defined.
Figure 17: Man operating a diaphragm pump machine	Error! Bookmark not defined.
Figure 18: Man scooping feacal sludge using a bucket	Error! Bookmark not defined.

List of tables

Table 1: show the components of the SSM machine	9
Table 2: shows the pump specifications	14
Table 3: Material specifications and their properties	22
Table 4: Equipment used in the machine fabrication	
Table 5: Shows the cost of materials	
Table 6: cost of labour	
Table 7: Shows the computation of salvage value	
Table 8: Shows the annual costs used in calculating the NPV value	
Table 9: Test results for testing the suction rotary vane compression system	
Table 10: Test results for the forklift	

Chapter one: Introduction.

This chapter entails the general information relevant to the research while clearly showing the problem of interest for the intended design. It includes how this study will help reduce the problems associated with faecal sludge management through fulfilling some of the listed objectives.

1.1: Background of the study.

In many developing countries, one of the biggest challenges facing urban settings is Faecal Sludge Management (FSM) where pit latrines fill faster than available capacities to empty, transport and safely treat or reuse the resulting sludge. Despite the progress, over half of the world's population, 4.2 billion people use sanitation services that leave human waste untreated, threatening human and environmental health (UNICEF, 2020). At the decline for meeting the MDGs in 2015, 2.1 billion (10⁹) people had gained access to improved sanitation. However, 4.5 billion people lacked access to safely managed sanitation (Scott, 2019).

Many countries depend on onsite sanitation facilities. Onsite sanitation technologies like flush toilets connected to septic tanks, pit latrines serve around 2.7 billion people (Strande, 2014). It is estimated that 90% of the waste generated is discharged to the environment untreated and this leads to a concern in financial sustainability in solid waste management in developing and transitional country cities (UN-HABITAT, 2010).

The elevated population in Kampala City causes deficient access to FSM facilities with an estimated percentage of Over 90% using pit latrines of inadequate standards, 45% of the pit latrines are abandoned after 5 years when either full or broken down due to inadequate O&M (Sanz Uriarte and Mujica, 2016).

When pit latrines fill, fecal sludge must be either safely sequestered in situ or must be hygienically emptied, safely transported and adequately treated for reuse or disposal (al R. D., 2020). The methods available for scooping sewage include manual emptying using buckets, spades, desludging pumps and vacuum tankers. The Gulper pump is the most widely used in East Africa due to its simple design

References

Nuwagaba, C. B. (2019). urban water journal. *Infrastructure investments and operating costs for fecal sludge and sewage systems in kampala uganda*.

Paul Lin, V. A. (2017). Different technologies for cooling compressors.

M. Grieb, A. Brümmer, International Conference on Screw Machines, 197–210 (Dortmund, Germany, 2014)

Aboulnaga, M. M., Badran, M. F., & Barakat, M. M. (2021). Global Informal Settlements and Urban Slums in Cities and the Coverage. In Resilience of Informal Areas in Megacities–Magnitude, Challenges, and Policies (pp. 1-51). Springer, Cham.

Gudda, F.O., Moturi, W.N., Oduor, O.S. *et al.* Pit latrine fill-up rates: variation determinants and public health implications in informal settlements, Nakuru-Kenya. *BMC Public Health* **19**, 68 (2019). https://doi.org/10.1186/s12889-019-6403-3

Lapworth, D.J., Nkhuwa, D.C.W., Okotto-Okotto, J. *et al.* Urban groundwater quality in sub-Saharan Africa: current status and implications for water security and public health. *Hydrogeol J* **25**, 1093–1116 (2017). https://doi.org/10.1007/s10040-016-1516-6

Kimbugwe, Ceaser and Musabe, Kenneth and Murungu, Ronnie, Survey on WASH Service Levels and the Enabling Environment for Provision of Sustainable Services in Kampala (November 27, 2018). OIDA International Journal of Sustainable Development, Vol. 11, No. 11, pp. 25-58, 2018, Available at SSRN: https://ssrn.com/abstract=3291289

Jennifer R. McConville, Elisabeth Kvarnström, James M. Maiteki & Charles B. Niwagaba (2019) Infrastructure investments and operating costs for fecal sludge and sewage treatment systems in Kampala, Uganda, Urban Water Journal, 16:8, 584-593, DOI: 10.1080/1573062X.2019.1700290

Gudda, F.O., Moturi, W.N., Oduor, O.S. *et al.* Pit latrine fill-up rates: variation determinants and public health implications in informal settlements, Nakuru-Kenya. *BMC Public Health* **19**, 68 (2019). https://doi.org/10.1186/s12889-019-6403-3

R.H Holm, W. C. (2017). Local solutions for emptying pit latrines in low income urban settlements. *Physics and chemistry of the earth* .

Thye, Y. P. (2009). pit latrine emptying technologies.

UN-HABITAT. (2010). solid waste management in world's cities.

UNICEF, W. (2020). state of the world's sanitation.

'Eruvin, T. S. and (2012) 'THE CONCEPT OF VISCOSITY', in, pp. 22–32. DOI: 10.1515/9783110289039.619.

Al-shamani, A. N. et al. (2013) 'Design & Sizing of Stand-alone Solar Power Systems A house Iraq', pp. 145–150.