

FACULTY OF ENGINEERING DEPARTMENT OF WATER RESOURCES AND MINING ENGINEERING

FINAL YEAR PROJECT PRESENTATION

PERVIOUS CONCRETE IN ROAD CONSTRUCTION AS A COST EFFECTIVE ALTERNATIVE FOR FLOOD CONTROL

CASE STUDY: QUEEN'S WAY, JUNCTION

BY

NANKABIRWA MELLISA N

BU/UP/2016/591

Tel; +256786090213/702632397

Email; mellisanankabirwa@gmail.com

AND

ORYEM JOSHUA OPIDO

BU/UP/2016/616

Tel; +256781117008/7505412971

Email;joshuaoryem@gmail.com

A final year project proposal report submitted to the Department of water resources and mining engineering in partial fulfilment for the award of the Bachelor of Science in Water Resources Engineering degree of Busitema University

ABSTRACT

Flooding is a very big problem in the biggest cities and major towns in Kampala Uganda and the whole world at large. This is of the increase in urbanization which involves many people moving to urban areas. In return there is a need to improve on the services like good transport routes to ease in the movements, in so doing the material used (Asphalt) for this cause is not friendly to the water cycle, the water meant to infiltrate into the soil is trapped on the surface as runoff and will result into flooding.

There is a need for a more sustainable road design and design and pervious concrete is a perfect solution to this major problem. It is a type of concrete with voids in it of about 25% to 30% voids ratio which allows a large amount of runoff to infiltrate.

Pervious concrete is made by mixing coarse aggregates, cement (OPC) water, Admixtures and HDPE for the case of our project. We came up with a pervious concrete road system that was able to allow 3.4litres of water infiltrate per second. With this result we believe pervious concrete is the way to go if we are to reduce the flooding hazard at Queens Way junction Kampala (our case study area for this research) and other parts of the world.

We had four objectives and achieved each one of them to be able to complete this project

The first objective was to determine the effective pervious concrete coefficient and we used software like EPANET, SWMM, Arc GIS, and google maps to achieve it. We got a pervious concrete coefficient of 0.89 which showed a gradual decrease in runoff to 35.4m³/sec hence flooding controlled.

The second objective was to obtain the optimum mix for the optimum mix ratios and to test for the pervious concrete properties. We did this by carrying out tests at Central materials laboratory in kireka and came up with a ratio of 1:0.45:4.05:0.5. This mix ratio enabled us to achieve the given strength and permeability of 32.5Mpa and respectively. We also carried out tests on each of the materials we used to come up with the pervious concrete system. Results of the laboratory test results are shown in the appendix.

The third objective was to design, simulate, construct and test the pervious concrete road system and we achieved this using software like Auto CAD and Solid works. We made design calculations for the layers of the road system that is the pervious concrete slab, the beams and the bottom impervious layer, we designed it in Auto CAD and used Solid works to do a simulation, we constructed the road system and tested for infiltration and found that it was efficient .

The fourth objective was to carry out the economic analysis and we found out that pervious concrete in road construction is far much cost effective compared to Asphalt and conventional concrete pavements.

In conclusion KCBA is located in a place with clayey soils and many impervious surfaces contributing so much to the flooding. But with this project in place we believe this hazard can be greatly reduced. This is seen in the entire report. "When it Rains it drains".

DECLARATION

I, NANKABIRWA MELLISA N, here by certify and confirm that the information I have

written in this project implementation report is a result of my own effort, research and has not

been submitted before to any university or institution of higher learning for any academic

award.

NANKABIRWA MELLISA

Signature: Date:

I, **ORYEM JOSHUA OPIDO**, here by certify and confirm that the information I have

written in this project implementation report is a result of my own effort, research and has not

been submitted before to any university or institution of higher learning for any academic

award.

ORYEM JOSHUA OPIDO

Signature: Date:

	_	_	_	_			_
			П	<i>(</i> 1)	177	· A	т
Δ	\mathbf{r}	М	к			Δ	

This report on using pervious concrete in road construction as a cost effective alternative for flood control has been written under the supervision of;

Main	Sin	pervisor
Main	Du	her Arsor

Name: Mr	MASERUKA BENDICTO
Signature:	Date

ACKNOWLEDGEMENT

We thank the Almighty God for the far that He has brought us, the gift of life, knowledge,

hope protection and his provision to us during and throughout the writing of this project report.

We extend our deep sense of gratitude and indebtedness to our academic supervisor, Mr.

Maseruka Bendicto for his time, kind attitude, keen interest, immense help, inspiration and

encouragement which helped me throughout this project proposal.

Sincere thanks to Mr. Kajubi Enock and Mr. Mr. Bagala Brian our consultants. I also thank the

entire staff of the department of Mining and Water Resources Engineering Busitema

University for providing all kind of possible assistance throughout this project proposal.

Special thanks to my family; Mr. Kaggwa John Bosco and Mrs. Namyalo Dorah Kaggwa, my

sisters, relatives and also the family of Mr. Opido Simon for their unconditional prayers, love,

care and guidance.

It would be great injustice if we omit the role played by our dear friends in directing us, their

tremendous tireless support and guidance given to us during the writing of this report.

Lastly, we thank all those who were involved directly or indirectly during our project report

writing.

May the good Lord reward you all!

DEDICATION

We dedicate this report to our parents for their unending support rendered unto us right from the proposal stage to the final implementation of this great project.

I also dedicate it to God for all the ideas and help He gave to us through the Holy spirit, May His name be glorified.

And finally to the Busitema University society of Engineers that is the Water and Mining Engineering Department and to all my friends who helped in all ways.

Thank you.

ACRONYMS

ACI American Concrete Institute

ASCE American Society of Civil Engineers

ASTM American Society of Test Methods

CP Concrete Practice

CRED Centre for Research on the Epidemiology of Disasters

DWRM Directorate of Water Resources Management

EPASWMM Environmental Protection Agency Storm Water Management Model

FFGS Flash Flood Guidance System

GFDRR Global Facility for Disaster Reduction and Recovery

GIS Geographical Information System

GPS Geographical Positioning System

HDPE High Density Propyl ethylene

IDF Intensity Duration Frequency

IS Indian Standard

KCBA Kampala Central Business Area

KCCA Kampala City Council Authority

MWE Ministry of Water and Environment

NGOs Non-Governmental Organisations

NOAA National Oceanic and Atmospheric Administration

NPV Net Present Value

NRMCA National Ready Mix Concrete Association

PC Pervious Concrete

PICP Permeable Interlocking Concrete Pavement

TRRL Transport and Road Research Laboratory

UNMA Uganda National Meteorological Authority

VDOT Virginia Department of Transportation

WMA Warm Mix Air

TABLE OF CONTENTS

Table of Contents

ABSTRAC	Γ	i
DECLARA'	TION	ii
APPROVA	L	iii
ACKNOWI	LEDGEMENT	iv
DEDICATI(ON	V
ACRONYM	1S	vi
TABLE OF	CONTENTS	vii
LIST OF FI	GURES	X
LIST OF TA	ABLES	1
CHAPTER	ONE	2
1.0 Ba	ckground	2
1.1 Proble	em statement	6
1.2 Justifi	ication	6
1.3 Objec	tives of the study	6
1.3.1 M	Tain objective	6
1.3.2 S	pecific objectives	6
1.4 Scope	e of the study	6
CHAPTER	TWO	7
2.0 Lit	erature review	7
2.1 Pream	nble	7
2.2 Flood	S	7
2.3 Curre	nt interventions to control floods	7
2.3.1 L	imitations in the current interventions (drainage systems)	9
2.3.2 A	sphalt and concrete roads	10
2.2 Th	e new intervention	10
2.2.1 P	ervious concrete	10
2.2.1	Current location and use	10
2.2.2	Advantages	11
2.2.3	Disadvantages	12
2.2.4	Other types used	12
2.2.5	High Density Propyl ethylene (HDPE)	13
2.4 SWN	M Structure and Theory	15

	2.4.1. Model Setup	16
	2.4.2. Model calibration and validation	16
	2.4.3. Hydrologic properties in SWMM	17
	2.4.4. SWMM hydraulics	18
	2.4.6. Other models used apart from SWMM	21
CH.	APTER THREE	22
3	.1 Methodology	22
	3.1.2 Study area description	22
	3.1.3 Effects of imperviousness on the hydrology parameters	22
	3.1.4 Tools used in the study	23
	3.1.5 Methods of data collection	23
3	.2 SPECIFIC OBJECTIVE ONE;	25
	3.2.1 Developing thematic maps for the watershed area	25
	3.2.1 DEM and slope creation	25
	3.2.2 ArcGIS Analysis and Catchment Delineation	25
	3.2.3 Assessing the runoff generated within the catchment.	25
	3.3.1 The runoff coefficient	26
	3.3.2 Rainfall intensity	26
3	.3 SPECIFIC OBJECTIVE TWO;	30
	3.3.1 Materials	30
	3.3.2 Properties of materials	32
	3.3.3 Mixture proportioning (NRMCA)	38
	3.3.5 Casting of test specimens	40
	3.3.6 Tests on the cast specimens.	40
3	.4 SPECIFIC OBJECTIVE THREE	45
	3.4.2 Designing the pervious road system	45
	3.4.4 The conceptual drawing	46
	3.4.5 The simulation process for the layers	46
	3.4.6 Construction process	46
3	.4.7 Testing	49
	3.4.8 Maintenance	50
3	.5 SPECIFIC OBJECTIVE FOUR	52
	3.5.1 Preamble	52
	3.5.2 Net present value	53
CЦ	ADTED EQUID: DDESENTATION AND DISCUSSION OF DESUITES	51

4.1 To determine the effective pervious coefficient for flood control of the area	54
4.1.1 Developing Thematic Maps of the Case Study Area	54
4.1.1 Catchment area	54
4.1.2 Land use map	54
4.1.3 Soil map	55
4.1.4 Slope map	56
4.1.5 Assessing the runoff generated within the catchment	57
4.1.6 IDF curves	58
4.1.7 Sub catchment runoff	58
4.2 To determine the optimum mix ratios and to test for the pervious concrete properties	s. 62
4.2.1 Material properties	62
4.2.2 Mix ratios	64
4.2.3 Test results on the cast specimens	65
4.3 To design and simulate the physical model of the pervious concrete road	70
4.3.1 Design of slab reinforcement	71
4.3.2 Conceptual Drawings of the pervious concrete pavement model	75
4.3.3 Simulation for structural analysis	77
4.3.4 Construction process of the pervious concrete road system	79
4.4 To determine the cost effectiveness of the pervious concrete	83
CHAPTER FIVE: CONCLUSIONS AND RECOMMENDATIONS	96
5.1 CHALLENGES	96
5.2 CONCLUSIONS	96
5.3 RECOMMENDATIONS	96
References	97
ADDENITIV	00

LIST OF FIGURES

Figure 0-1: Plot showing precipitation depths against return periods	. 26
Figure 2: showing a falling head apparatus.	. 44
Figure 3: showing the pervious road system	. 46
Figure 4 showing a map of land use land cover of Kampala	. 55
Figure 5 showing a map of Kampala with different soil types	. 56
Figure 6 A map showing the slope of the catchment area	. 57
Figure 7 showing line graph of porosity against total runoff.	. 59
Figure 8 showing bar graph of porosity against total runoff	. 59
Figure 9showing a graph plotted from SWMM of runoff against the elapsed time	. 60
Figure 10 Shows reduced flooding in the area under study.	. 60
Figure 11 Shows a red node signifying flooding with reduced permeability	. 61
Figure 12 Shows a reduction in the flooding with increase in permeability	. 61
Figure 13 Further reduction in the flooding as permeability increases hence a green node	. 62
Figure 14 Shows greater reduction in the flooding as permeability increases hence a blue no	ode.
	. 62
Figure 15 A graph showing compressive strength at 7 and 28 days	. 68
Figure 16 showing the 3D drawing of the pervious road system	. 76
Figure 17 Full conceptual of the pervious road	. 76
Figure 18 showing the slab design	. 76
Figure 19 showing the beam	. 77
Figure 20 Showing the road under dispplacement	. 77
Figure 21 Showing the road under stress	. 78
Figure 22 showing the road under strain	. 78
Figure 23 Showing the pervious road under loading	. 79
Figure 24 showing Rigid and Flexible pavements	. 83
Figure 25 showing VICAT apparatus for cement test	. 99
Figure 26 showing the pervious road system model	. 99
Figure 27 showing form work	. 99
Figure 28 showing plastic HDPE pellets after molding	. 99
Figure 29 showing sieve analysis test in progress	. 99
Figure 30 show plastic HDPE flakes before molding	. 99

LIST OF TABLES

Table 1: showing the various hydrologic and hydraulic models	21
Table 2: showing the tools to be used in the study	23
Table 3: showing the data sets required	24
Table 0-3: Daily rainfall intensity for the different return periods.	27
Table 5: showing typical ranges of materials proportions in pervious concrete (NRMCA) 40
Table 6: showing the specimen tests	45
Table 7: showing the costs involved in road construction	53
Table 8: Showing results from SWMM simulations	58
Table 9 Showing table of cement	63
Table 10 Test results of coarse aggregate	63
Table 11 Showing test results of fine aggregates	63
Table 12 showing test results of HDPE	64
Table 13 Showing samples series with Perentage Variation of HDPE	64
Table 14 Showing Compressive strength at 7 and 28 days	65
Table 15 summary of the compressive strength test	67
Table 16 porosity results	68
Table 17 showing permeability results	69
Table 18 Table showing different K values for the soil types	71
Table 19 showing shear and strain table	74
Table 20 results of bar spacing, area of steel and diameter of the steel used in the reinforce	ement
	74
Table 21 showing bar spacing, Area of steel and Diameter of the steel in the beam	75
Table 22 Showing materials used in our project	83
Table 23 Showing initial cost for the construction of Asphalt road	85
Table 24 showing cost of the materials	87
Table 25showing materials use for Asphalt pavements	88
Table 26 showing cost of materials used for Asphalt	88
Table 27Quantities obtained from measurements for pervious concrete	89
Table 28Cost for pervious concrete	89
Table 29 Showing economic comparison of the roads	95